See Why the New 1500 is Better		
BatteryMINDer 1500 vs. BatteryMINDer <u>Plus</u> 12117		
Features	1500	12117
	ENERGY STAR	
Description	Maintenance Charger-Desulfator	Maintenance Charger-Desulfator
Voltage	12V	12V
Amps	1.5 Amps	1.33 Amps
Power Source	100-240 VAC; 50/60 Hz	120 VAC; 60 Hz
Temperature Compensation	Yes	No
Bad Cell Detection	Yes	No
Minimum Start Up Battery Voltage	3 Volts	10.5 Volts
5-Stage Charger	Yes	No
Plug 'n Run "no buttons"	Yes	No
Form factor	Wall Plug-In	Wall Plug-In
cULus/ETL	Yes	Yes
Energy Star / CEC 📧	Yes	No
Automatic pulse desulfation	Yes	Yes
Ambient Temperature Sensor (ATS-1)	Included, installed	No
Battery Clips (BC-2410)	Included	Included
Ring Terminal Assembly (RTA-2410)	Available as an optional accessory	Included
Optional mounting clips	Included	No
Multiple batteries (Qty.)	4 as a Maintainer. Requires use of Y-Connectors 210AY (sold separately) or customer's supplied 18 gauge wire.	4 as a Maintainer. Requires use of Y-Connectors 210AY (sold separately) or customer's supplied 18 gauge wire.
Works with Battery Types	12 volt Flooded (filler caps), Sealed, Maintenance-free, Starter, Deep Cycle, Marine, Hybrid and Optima brand Sealed AGM	12 volt Flooded (filler caps), Sealed, Maintenance-free, Starter, Deep Cycle, Marine, Hybrid
Guarantee/ Warranty	1 Year Unconditional / 5 Year "No Hassle"	1 Year Unconditional / 5 Year "No Hassle"
MSRP	\$54.95	\$69.95